

Dock Gates (Lazy Tong):

Singles:

- Standard stock heights available: 6', 6'6", 7', 7'6", 8' in use.
- Specify lock left or lock right.
- Single gates less than 6'6" tall in use are UPS shippable.
- Gates pivot 180 degrees.
- Included with gate: 48" locking bar, DVD installation video, instruction sheet, one washer, one 2" L bracket.

4'-6' Wide – Standard features.

7'-11' Wide – Includes one drop pin.

11'-12' Wide – Two drop pins, one center axle 14" wide.

Gate is shipped in two pieces and must be bolted together on site with three carriage bolts, washers and nuts (provided).

Pairs:

- Standard stock heights available: 6', 6'6", 7', 7'6", 8' in use.
- All pairs have a center cane bolt.
- Gates pivot 180 degrees.
- Included with gate: DVD installation video, instruction sheet, two washers and two 2" L brackets.

8'-12' Wide – Standard features.

12'-20' Wide – Two drop pins.

20'-24' Wide – Four drop pins, two center axles 14" wide.

The gate is shipped in four pieces and must be bolted together on site with six carriage bolts, washers and nuts (provided).

Dock Gates – Specials:

- Maximum height on all dock gates is 12' collapsed, 11'6" in use.
- Maximum width is 12' on singles and 24' on pairs.

Door Gates (Lazy Tong):

- Available in one standard width, 48".
- Heights available: 31", 33", 37", 40", 43", 46", 49", 51", 59", 61", 63", 66", 71", 73", 76", 79", 81", 83".
- One 48" locking bar is standard.
- Gate is hinged, specify lock left or right.
- Included with gate: instruction sheet and DVD installation video.

Top Track Gates (Lazy Tong):

- Maximum height is 11'6" in use. Note that the top track can be mounted higher than the gate.
- Top track gates have no maximum width.
- These gates do not pivot out of the opening. Stack in line only.
- Gates can be face mounted to the wall, mounted directly to a ceiling or attached to free standing posts.

Bottom Guide Gates (Lazy Tong):

- Specify face mount or in jamb.
- Maximum height is 11'6" in use, minimum 31".
- Maximum width is 8' for singles and 16' for pairs.
- These gates pivot out of the opening when not in use.

Portable XL Series Gates (Lazy Tong):

- 6', 6'6", 7', 7'6", 8' tall in use.
- Standard width maximum 12'. • Stack space 27".
- Shipped unassembled. Included with gate: two 12" locking bars, instruction sheet, DVD installation video, three braces, box of hardware (three axles, three flathead bolts, six casters, six nuts for casters, five 3/4" bolts, five 1/4" nuts and washers.)
- Portable add on's maximum width 6'. Add on's come with: brace, hardware (axle, flathead bolt, two casters, two 1/2" nuts for casters, four 3/4" bolts, four nuts, four washers, 12" locking bar), instruction sheet and DVD installation video.
- Can be attached together to form gates with no maximum width.

Barrier Gates are 47" high in use and a maximum of 12' long. Add on's available in 6' lengths and can be bolted together to create the length you need. Two locking bars are provided. Use as a barrier to direct traffic or prevent someone from getting too close to a hazardous area. Standard colors are black and yellow.

Aisle Gates are 40" high in use and a maximum of 84" wide. They do not have axles, only feet and can be easily lifted and moved from one area to another. Designed to be attached to one another. Standard color is yellow.

Xtra Duty Gates (Bostwick):

- Xtra Duty gates do not lose any height when the gate is extended.
- Vertical channels are attached to one another with shears. Two rows of shears are provided for gates 5'-8' high, gates 8'-12' have three rows of shears.
- A cylinder lock is standard on all models (cylinders cost extra and can be keyed, blank or thumb turn).
- More than twice the weight and strength of a standard lazy tong gate.
- If both tracks are folding, the entire gate with the tracks can pivot out of the opening.
- With single gates a locking bar equal to the height of the gate is attached to the wall opposite the side where the gate is attached. With pair gates, the locking bar is integrated into the design.

Fixed Top Track, Folding Bottom Track:

- Track can be mounted to the ceiling or face mounted to the wall with special angle brackets.
- Maximum height 12', minimum 5'.
- Maximum width – single 16', pair 32'.
- Available to stack in line or pivot.

Fixed Top Track (Self Supporting), Folding Bottom Track:

- Top track is self supporting.
- Maximum height 12', minimum 4'.
- Maximum width single 16', pair 20'.
- Available to stack in line or pivot.

Folding Top Track, Folding Bottom Track:

- Maximum height 8', minimum 5'.
- Maximum width single 16', pair 20'.
- Available to stack in line or pivot.

Xtra Duty Portables:

- Height 6'6". • Width 3'-6', 6'-9', 7'-12', 11'-15', 13'-18'.
- 3 Models:
Wall mount – comes with two 6" locking bars.
Floor mount – comes with two brass floor anchors.
Pressure fit – no mounting hardware required, locking mechanism creates pressure on opposing walls with rubber bumpers. Gate can be locked in a pressurized position.
- Shipped assembled.



**ILLINOIS
ENGINEERED
PRODUCTS**