

**ON THE
MOVE
SECURITY!**


Portable Gates

Heavy-Duty Security on Demand



A Quick and Simple Way to Temporarily Seal off any Area

- Moveable access control & security
- Protect property & merchandise
- High visibility of secured spaces
- Limit access to machinery & hazardous areas
- Use in multiple locations & applications
- Custom powder coat colors available
- 100% made in America



**ILLINOIS
ENGINEERED
PRODUCTS**

The Preferred Security Gates for Protecting Businesses Since 1962

Access Control Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
XL1265	up to 12'	6'	6' 6"	27"	135
XL665	adds up to 6'	6'	6' 6"	11"	64
XL1275	up to 12'	7'	7' 6"	27"	146
XL675	adds up to 6'	7'	7' 6"	11"	70

Specifications

Finish: Galvanized, Powder Coat Colors Available

Webbing: 3/8" x 3/4" 14-gauge

Frame: 1 1/2" x 1 1/2" 12-gauge Angle Iron

Locking Bar: 1 1/2" x 1 1/2" 12-gauge Angle Iron

Hasp: 3/16" Steel Welded to Frame*

Support Bars: 3/4" Round Steel Tubing

Axle: 24" Wide with 11-gauge Steel

Caster: 3" Locking Rubber Casters

Rivets: 3/16" x 1/2" Steel

**Padlock not included*

Starter & Add-ons: Use Alone, or Attach Add-on to Starter Gate Providing an Additional 6' in Width. Unlimited Add-on Gates can be Connected.

ECO™ Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
XLEC01265	up to 12'	6'	6' 6"	27"	90
XLEC0665	adds up to 6'	6'	6' 6"	11"	45

Specifications

Finish: Galvanized Webbing, Gray Powder Coated Frame

Webbing: 3/8" x 3/4" 16-gauge Steel

Frame: 1 1/2" x 1 1/2" 13-gauge Angle Iron

Locking Bar: 1 1/2" x 1 1/2" 13-gauge Angle Iron

Hasp: 3/16" Steel Welded to Frame*

Caster: 2 1/2" Rubber Casters

Rivets: 3/16" x 1/2" Steel

**Padlock not included, Cylinder Lock optional*

Barrier Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
XL1240	up to 12'	41"	47"	27"	90
XL640	adds up to 6'	41"	47"	11"	40

Specifications

Finish: Galvanized, Yellow and Black Powder Coat

Webbing: 3/8" x 3/4" 14-gauge

Frame: 1 1/2" x 1 1/2" 12-gauge Angle Iron

Locking Bar: 1 1/2" x 1 1/2" 12-gauge Angle Iron

Hasp: 3/16" Steel Welded to Frame*

Axle: 14" Wide 11-gauge Steel, 3 Axles per Gate

Caster: 3" Locking Rubber Casters

Rivets: 3/16" x 1/2" Steel

Straps: 10" Long x 1 1/2" Wide, 14-gauge CRS

**Padlock not included, Cylinder Lock optional*

Starter & Add-ons: Use Alone, or Attach Add-on to Starter Gate Providing an Additional 6' in Width. Unlimited Add-on Gates can be Connected.

Aisle Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
Aisle Gate	7'	40"	40"	7"	12

Specifications

Finish: Galvanized, Safety Yellow Powder Coated

Webbing: 3/8" x 3/4" 14-gauge Steel

Frame: 1 1/2" x 1 1/2" 12-gauge Angle Iron

Handle / L-pin: 5/8" Steel – Use as a Handle or to Attach Multiple Gates

Feet: 14" Wide, 11-gauge Steel

Rivets: 3/16" x 1/2" Steel

Multiple Aisle Gates can be hooked together to form corners or any length. Light weight and welded on handle makes it easy to move from area to area.

Accessories

Padlock: 2" Hardened Steel with Plated Shackle

8' Post: Lock Gate to Posts Instead of Wall or Casing

IEP Safety + Security Products are exclusively sold by IEP Authorized Dealers.



Portable Access Control Gate (Starter)



Portable Barrier Gate (Starter)



Portable Aisle Gate (Starter)

